

MV 160 Series



Application

- Decoration of supply and exhaust vents of public, residential and industrial ventilation systems.
- Used for correct air flow distribution in premises.
- Wall or ceiling mounting.

Design

- Made of quality and durable plastic.
- Multi-element structure. The internal part is fixed to the base with latches for easy cleaning without dismantling.
- Fixing with screws or lugs depending on grille modification.

Colour modifications



Modifications

MV 160 - basic modification



- Screw fixing.
- **MV 160 s** - model with a protecting insect screen and screw fixing.
- **MV 160 M** - model with fixing lugs.
- **MV 160 Ms** - model with fixing lugs and a protecting insect screen.



MV 160 VD - model with four-element connecting flange (VD)



- Screw fixing.
- Equipped with four-element connecting flange with adjustable diameter for connection to \varnothing 100-150 mm round air duct.
- **MV 160 VDs** - model with four-element connecting flange and a protecting insect screen.
- **MV 160 VDM** - model with four-element connecting flange and fixing lugs.
- **MV 160 VDMs** - model with four-element connecting flange, fixing lugs and a protecting insect screen.



Overall dimensions

| Model | Dimensions, mm | | | | | | | Air pass, m ² | Fig. no. |
|-----------|----------------|-----|----|----|-----|-----|---------|--------------------------|----------|
| | H | B | L | L1 | H1 | B1 | D | | |
| MV 160 | 299 | 221 | 15 | - | 283 | 205 | - | 0,026 | 1, 2 |
| MV 160 VD | 299 | 221 | 15 | 42 | 283 | 205 | 100-150 | 0,026 | 1, 3 |




Fig. 1




Fig. 2




Fig. 3