

Description


Aluminium sealing tape with a thickness of 30 microns. Used at joining points of round ducts and fittings, and in flexible ducts.

Temperature resistances depend on the type of tape and are shown in the table.

Note: For tapes retained their adhesive properties should be kept at about 21°C and should not exceeding 50%. It must be protected from sunlight.

Example identification

Product code: **TAL 50 - 50**



Dimensions



Code	width B [mm]	length [mb]	packaging [pcs]	temp [°C]
TAL-50-50	50	50	24	80
TAL-75-50	75	50	16	80
TAL-100-50	100	50	12	80
TAL-50-10	50	10	272	80

thickness of 30 microns

Code	width B [mm]	length [mb]	packaging [pcs]	temp [°C]
TAL-50-50	50	50	24	80
TAL-75-50	75	50	16	80

thickness of 40 microns

Code	width B [mm]	length [mb]	packaging [pcs]	temp [°C]
TAL-15 50-50	50	50	24	150
TAL-15 75-50	75	50	16	150
TAL-15 100-50	100	50	12	150

thickness of 30 microns

Code	width B [mm]	length [mb]	packaging [pcs]	temp [°C]
TAL-25 50-50	50	50	24	250
TAL-25 75-50	75	50	16	250
TAL-25 100-50	100	50	12	250
TAL-25-50-10	50	10	72	250

thickness of 30 microns